



CURVE A 90° PN 6 - SERIE DUO

ECOPEX® DUO - RISCALDAMENTO PN 6 - ISOLAMENTO STANDARD

Tipo [mm]	PE-Xa Pipe				PE Casing		Peso curva [kg]
	DN/pollici	d _{int} [mm]	s [mm]	d _{ext} [mm]	D _e [mm]	s _p [mm]	
25+25/90	20+20 - 2x3/4"	20,4	2,3	25	110	3,0	4,67
32+32/110	25+25 - 2x1"	26,2	2,9	32	110	3,0	4,71
40+40/125	32+32 - 2x1" 1/4	32,6	3,7	40	125	3,0	7,42
50+50/160	40+40 - 2x1" 1/2	40,8	4,6	50	160	3,0	9,90
63+63/180	50+50 - 2x2"	51,4	5,8	63	180	3,0	13,20
75+75/200	65+65 - 2x2" 1/2	61,4	6,8	75	200	3,0	15,00

ECOPEX® DUO - RISCALDAMENTO PN 6 - ISOLAMENTO PLUS

Tipo [mm]	PE-Xa Pipe				PE Casing		Peso curva [kg]
	DN/pollici	d _{int} [mm]	s [mm]	d _{ext} [mm]	D _e [mm]	s _p [mm]	
25+25/90	20+20 - 2x3/4"	20,4	2,3	25	110	3,0	5,67
32+32/110	25+25 - 2x1"	26,2	2,9	32	125	3,0	5,71
40+40/125	32+32 - 2x1" 1/4	32,6	3,7	40	160	3,0	8,42
50+50/160	40+40 - 2x1" 1/2	40,8	4,6	50	180	3,0	10,90
63+63/180	50+50 - 2x2"	51,4	5,8	63	200	3,0	14,20