



VORISOLIERTE 90° BOGEN 10 BAR - DUO

ECOPEX® DUO - SANITÄR 10 BAR - STANDARDISOLIERUNG

Typ [mm]	PE-Xa Pipe				PE Casing		Gewicht [kg]
	DN/Zoll	d _{int} [mm]	s [mm]	d _{ext} [mm]	D _e [mm]	s _p [mm]	
*25+20/90	20+15 - 3/4" + 5,8"	18 - 14,4	3,5 - 2,8	25 - 20	90	3,0	3,50
32+20/110	25+15 - 1"+5/8"	23,2 - 14,4	4,4 - 2,8	32 - 20	110	3,0	5,00
40+25/125	32+20 - 1"1/4+3/4"	29 - 18	5,5 - 3,5	40 - 25	125	3,0	6,50
50+32/125	40+25 - 1"1/2+1"	36,2 - 23,2	6,9 - 4,4	50 - 32	125	3,0	7,30

* = Durchmesser als Richtwert; entweder Ø 22 oder Ø 28

ECOPEX® DUO - SANITÄR 10 BAR - STANDARDISOLIERUNG

Typ [mm]	PE-Xa Pipe				PE Casing		Gewicht [kg]
	DN/Zoll	d _{int} [mm]	s [mm]	d _{ext} [mm]	D _e [mm]	s _p [mm]	
25+20/110	20+15 - 3/4" + 5,8"	18 - 14,4	3,5 - 2,8	25 - 20	110	3,0	4,50
32+20/125	25+15 - 1"+5/8"	23,2 - 14,4	4,4 - 2,8	32 - 20	125	3,0	6,00
40+25/140	32+20 - 1"1/4+3/4"	29 - 18	5,5 - 3,5	40 - 25	140	3,0	7,80
50+32/160	40+25 - 1"1/2+1"	36,2 - 23,2	6,9 - 4,4	50 - 32	160	3,0	8,80